



Standards For Safety : Close Top Diked(contained)

1. UL 142 : Steel Above Ground Tanks for Flamable and Combustible Liquids
2. CAN/ULC-S601 : Shop Fabricated Steel Above Ground Tanks for Flamable and combustibile Liquids

PROPRIETARY AND CONFIDENTIAL
This drawing and its contents are the proprietary and confidential information of Western International, Inc., and are not to be reproduced, copied, or publicly disclosed. If this drawing is provided to a someone outside Western International, it is done so for the limited purpose of assisting that recipient with a technical or product issue. In receiving this drawing, the recipient agrees to maintain it in confidence and not to use it beyond the purpose previously stated. Recipient agrees not to reproduce, copy, or publicly disclose this drawing and its contents.

UNLESS OTHERWISE SPECIFIED:
DO NOT APPLY TO BASIC DIMS.
TOLERANCES (INCHES):
ONE DECIMAL ±.1"
TWO PLACE DECIMAL ±.06"
THREE PLACE DECIMAL ±.030"

TOLERANCES (METRIC):
ONE DECIMAL ±.5
TWO PLACE DECIMAL ±.05
ANGULAR: BEND ±1°

TITLE:

FCP500-SALES DRAWING

MATERIAL
SEE INDIVIDUAL PARTS

SIZE
B

DWG. NO.
FCP500

REV
1

DO NOT SCALE DRAWING

DRAWN BY: JIGNESH

DATE: 1/2/2013

SCALE: 1:24

SHEET 1 OF 3

DIESEL DIRECT®