

DRY EDGE[®]

by **DIESEL DIRECT[®]**



Diesel Direct's proprietary formula is designed to solve issues associated with diesel's number one enemy: water. Dry Edge provides enhanced moisture control and can reduce water contamination in fuel tanks, generators, and storage tanks.

Product Benefits:

- + When used consistently, works to eliminate moisture and water buildup in bulk storage and saddle tanks
- + Helps remove water from the fuel system
- + Can inhibit the growth of bacteria and microbial contamination

- + Moisture control helps prevent fuel system icing
- + Complements Diesel Direct's RoadChamp[®]
- + Free of harmful alcohols & effective in all diesel fuels including ULSD, biodiesel blends, and 100% diesel



RECOMMENDED USAGE:

FOR BULK TANK TREATMENT: 1 gallon of Dry Edge treats 1,000 gallons of ULSD. Pour Dry Edge into the tank prior to loading fuel. Fill tank to capacity with diesel fuel.

FOR VEHICLE TANK TREATMENT: 1 quart of Dry Edge treats 250 gallons of ULSD. When tank is empty, pour Dry Edge into the tank and fill tank to capacity with diesel fuel.

* Any bottom water should be pumped from either bulk or saddle tanks prior to product use.

Typical Properties

Appearance	Clear liquid
Specific Gravity, 68°F	0.902
Density, lb./gal, 68°F, (20°C)	7.53 lbs./gal
Flash Point, PMCC, °F	148 F
Pour Point, °F	<-40F
Viscosity, cSt @ (68°F, 20°C)	3.3 cSt